

# Sobo S Gold 08



## Oil Platform Rigwash – OCNS Gold Standard



**An Internationally approved (OCNS Gold Standard) offshore rigwash and oil degreaser that efficiently removes oil and grease contamination.**

Sobo S Gold 08 contains a blend of biodegradable surfactants and wetting agents and is registered for use in offshore installations.

- OCNS Gold approved - with no product warnings
- ph <9
- Marine friendly
- Low to medium foamer
- Separator friendly

### Why choose Sobo S Gold 08?

- **Fast & powerful**
  - Quickly removes grease & oil contamination
- **Approved for offshore use**
  - OCNS Gold Standard with no product warnings
- **Approved in Norway**
  - Registered for offshore use (OCNF)
- **Emulsion free**
  - Rapid separation of oil phase from rinse water
- **Medium foamer**
  - Shows where you have cleaned without excessive foaming
- **Economical - capable of significant dilution**
  - Standard dilution rate of 2 - 6%



# Sobos Gold 80

## WHERE TO USE

An Internationally approved (OCNS Gold Standard) offshore Rigwash and oil degreaser. Use for general purpose cleaning and degreasing of equipment, machinery and surfaces. Also suitable for use as an industrial laundry additive.

## HOW TO USE

- Apply by either contact, dip, immersion or spray application.
- Use as supplied for heavy duty degreasing.
- Allow a contact time of 2-3 minutes, then rinse with clean water.
- Dilute to 4-6% for general rig wash activity and janitorial cleaning.
- Dilute to 2-4% when used as an industrial laundry additive.
- Maximum dilution: 0.5% (1:200).

## INTERNATIONAL REGISTRATIONS

- OCNS Gold Registration No. 23125
- Norway OCNF PRN 304643
- Denmark Miljøstyrelsen PRN 2100911

## PHYSICAL PROPERTIES

• Appearance	Pale yellow liquid
• Specific gravity	1.05
• pH	~9.0
• Viscosity	Non-viscous
• Flash point (°C)	>93
• VOC content	Zero

## ENVIRONMENTAL IMPACT

- Biodegradable
- No bioaccumulation potential
- VOC free
- Negligible ecotoxicity

## STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers off the ground and out of direct sunlight. Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

## DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

## TECHNICAL SERVICES AND SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515. Oil Technics Ltd manufacture in Scotland under ISO 9001: 2015 and ISO 14001: 2015 accredited management systems.

## PACK SIZES

Available in the following sizes:

- 4 x 5 Litre containers
- 25 litre containers
- 200 litre drums
- 1000 litre IBCs



## Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH

T: +44 (0) 1561 361515 E: info@oiltechnics.com W: oiltechnics.com

Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.

