

# Sobo Degreaser

## Heavy Duty Oil Degreaser



**A general purpose heavy duty aqueous degreaser, designed to remove oils, greases and lapping slurry.**

Ideal for the degreasing of engineering components, work shops, industrial floors and similar areas contaminated by heavy oil and grease.

- Heavy duty oil degreaser
- Biodegradable
- Water rinsable

### KEY PROPERTIES

An aqueous blend of biodegradable surfactants that quickly lift and separate oil contamination from industrial components. Water rinsable to provide an oil free clean surface.

### APPROVALS

- Separator Friendly: meets pr EN 858

### APPLICATION

- Designed for use in either a contact wipe, dip, immersion or spray on application.
- Allow a contact time of 2 – 3 minutes before rinsing surfaces with water.
- Recommended dilution rate: 4%.
- Minimum dilution rate: 0.5%.
- Dilutions below 10% are not classified as hazardous.

### TECHNICAL DATA

<b>Appearance</b>	Pale yellow liquid	<b>SG</b>	1.08
<b>VOC Content</b>	Negligible	<b>pH</b>	>11.5
<b>Flash point</b>	>93°C	<b>BOD/COD 5 day</b>	72%

### PACKAGING

1000L, 200L, 25L and 4 x 5L containers.

### SAFE HANDLING AND STORAGE

Store in original containers and avoid extremes of temperature. For guidance on handling and disposal see Safety Data Sheet.

Manufactured and supplied by

#### **Oil Technics Ltd.**

Linton Business Park, Gourdon,  
Aberdeenshire, Scotland UK DD10 0NH

**Tel:** +44 (0) 1561 361515

**Fax:** +44 (0) 1561 361001

**Email:** info@oiltechnics.com

**Web:** www.oiltechnics.com



FM 696382

EMS 696323

