

# Sobo Power



## Versatile, Biodegradable Alkaline Degreaser & TFR



**A truly powerful product that rapidly degreases the heaviest of oil contaminated yards, factory floors and engineering components.**


**Versatile because Sobo Power is also an excellent Traffic Film Remover - making it our chemical of choice for cleaning cars and lorries traffic film free.**

A blend of biodegradable surfactants designed to reduce the surface tension of oil and grease emulsions, enabling surfaces to be rinsed clean, oil free and film free.

- Removes oils, diesel and lapping slurry
- Excellent TFR
- Versatile
- Biodegradable
- Separator friendly

### SOBO POWER: BEFORE & AFTER

**BEFORE**



**AFTER**



**BEFORE**



**AFTER**



### HOW TO USE

- Apply via pressure washer, steam cleaners, floor scrubbing equipment or manually.
- Can be use in either cold or hot water.
- Recommended start solution: **4%** (1:25).
- Maximum dilution: **0.5%** (1:200).
- For use as a TFR: use dilutions **>20%** (1:5).
- Allow a contact time of 2–3 minutes before rinsing clean with water.
- Can be used as supplied for very heavy oil degreasing.

### PHYSICAL PROPERTIES

Appearance	Pale green liquid*
Specific gravity	1.06
pH	>11.5
Flash point (°C)	>93
VOC content	Negligible
BOD <sub>5</sub> / COD	>50%

### ENVIRONMENTAL IMPACT

- Readily biodegradable
- Negligible VOC content • Negligible ecotoxicity
- No bioaccumulation potential

### DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

### STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

### TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

### PACK SIZES

- 4 x 5 Litre containers
- 20 litre containers
- 200 litre drums
- 1000 litre IBCs

\* Please note colour may fade over time: this does not effect the product's performance.



### Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | [info@oiltechnics.com](mailto:info@oiltechnics.com) | [oiltechnics.com](http://oiltechnics.com)



Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.