Sobo UL



Aqueous Ultrasonic Cleaning Fluid




A biodegradable water based cleaning additive specially designed for use in ultrasonic cleaning baths, Sobo UL quickly and efficiently removes oil, grease and cutting fluids.

Sobo UL removes a wide variety of soils including oil, grease and particulates and is excellent at removing neat soluble and synthetic cutting fluids. Suitable for engineering parts and electrical components, Sobo UL is also ideal for cleaning jewellery.

- Good cavitation
- Multi-metal, plastic and rubber compatible.
- Corrosion protected
- Non-flammable
- Water rinsable







HOW TO USE

- Use diluted in ultrasonic cleaning machines.
- Can be used at temperatures up to 70°C.
- At >60°C, use at dilutions of **4%** (1:25).
- At ambient temperatures, use at dilutions of **10%** (1:9).

PHYSICAL PROPERTIES

Appearance	Colourless liquid
Specific gravity	1.029
рН	~10.0
Flash point (°C)	>93

ENVIRONMENTAL IMPACT

- Biodegradable
 Negligible ecotoxicity
- No bioaccumulation potential

DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
- 200 litre drums
- 20 litre containers
- 1000 litre IBCs









Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com











