

Sobo UL

Aqueous Ultrasonic Cleaning Fluid



A water based cleaning additive for use in ultrasonic cleaning baths. Removes oil, grease and cutting fluids efficiently and quickly.

KEY PROPERTIES

- Water based degreaser with excellent cavitation and cleaning properties.
 - Specially designed for use in ultrasonic baths.
 - For the removal of a wide variety of soils including oil, grease and particulates.
 - Excellent at removing neat soluble and synthetic cutting fluids.
 - Corrosion inhibited and multi metal, plastic and rubber compatible.
 - Suitable for engineering parts and electrical components.
 - Also ideal for cleaning jewellery.
 - Can be used at temperatures up to 70°C.
- Good cavitation
 - Non-flammable
 - Water rinsable
 - Safe to use
 - Corrosion protected
 - Biodegradable

APPLICATION

- Use diluted in ultrasonic cleaning machines.
- At 60°C, use dilutions of 1:24 (4%).
- At ambient temperatures, use at dilutions of 1:9 (10%).
- Dilutions below 1:1 are not classified as hazardous.

TECHNICAL DATA

Appearance	Colourless liquid	SG	1.03
Flash point	> 93°C	pH	9.0
VOC	< 10%		

PACKAGING

200L, 25L, 4 x 5L

SAFE HANDLING AND STORAGE

Store in original containers and avoid extremes of temperature. For guidance on handling and disposal see Material Safety Data Sheet.



Manufactured and supplied by

Oil Technics Ltd.

Linton Business Park, Gourdon,
Aberdeenshire, Scotland UK DD10 0NH

Tel: +44 (0) 1561 361515

Fax: +44 (0) 1561 361001

Email: info@oiltechnics.com

Web: www.oiltechnics.com



ISO 9001
FM 26186

ISO 14001
EMS 575901